


Certification / Sertifikasyon



Max. Number of User / Maksimum Kullanıcı Sayısı



- * **Material /Malzeme:** ST 37 Steel / ST 37 Çelik
- * **Lenght/ Uzunluk:** 80 cm to 230 cm / 80 cm'den 230 cm'e.
- * **Strenght / Mukavemet:** 13 kN
- * **Max. User / Maks. Kullanıcı:** 2 persons / 2 kişi
- * **Standard / Standart:** EN795/A:2012, CEN/TS 16415/A:2013 tested, approved, and certified by QUINTIN CERTIFICATIONS

(EN) OD-EXT has been specially designed to be mounted on all kinds of structural elements, especially marine type vertical ladders with R&D studies and experience. The user can safely complete his ascent and descent with the EN 360 standard retractable fall arrest to be mounted according to the height of the ladder and / or the height to be climbed. It has been developed as an alternative solution in order to reduce the extra investment and operating cost brought by the vertical lifeline, and it is a user-friendly product that improves the costs of enterprises and offers ease of use to the personnel.

(TR) OD-EXT, Ar-Ge çalışmaları ve tecrübe birikimi ile gemici tip dikey merdivenler başta olmak üzere her türlü yapı elemanına ankraj noktası oluşturması ve montajlanabilmesi için özel olarak tasarlanmıştır. Merdiven yüksekliğine ve/veya çıkılacak yükseklik metrajına göre montajlanacak EN 360 standardına sahip geri sarımlı düşüş durdurucu ile kullanıcının tırmanışını ve inişini güvenle tamamlamasını sağlamaktadır. Kalıcı dikey yaşam hattının getirdiği ekstra yatırım ve işletme maliyet yükünü azaltmak amacıyla alternatif çözüm olarak geliştirilmiştir ve işletmelerin maliyetlerini iyileştiren ve personele kullanım kolaylığı sunan kullanıcı dostu bir üründür.

